



O-Eazy Series

Reliable PV Power for Solar Home Systems and Pay-As-You-Go Systems

Modules with Smart Z-frame – O-Eazy Series for SHS and PAYG Systems



Available as 5Wp, 12Wp, 25Wp, 40Wp, 2x25Wp, and 2x40Wp to suit your off-grid system requirement.



O-Eazy with patented Z-frame can be easily installed from front side.



Features: dust removal, wind ventilation, anti-moisture, mechanical stress simulation, and durability test.




Smart Z-type
Frame



Easy Installation By
Pull-Out Fitting



Dust Removal/
Wind Ventilation



Mechanical Stress
Simulation / Durability Test

O-Eazy Series | Smart Z-frame Design for SHS and PAYG Systems

Model Name		OZP0050 / OZM0050	OZP0120 / OZM0120	OZP0250 / OZM0250	OZP0400 / OZM0400	OZP0500 / OZM0500	OZP0800 / OZM0800	
ELECTRICAL CHARACTERISTICS	P _{max} (W)	5.0	12.0	25.0	40.0	50 (2x25)	80 (2x40)	
	V _{mpp} (V)	6.11	18.33	18.33	18.47	18.33	18.47	
	I _{mpp} (A)	0.82	0.65	1.36	2.17	2.72	4.34	
	V _{oc} (V)	7.54	22.6	22.6	23.04	22.6	23.04	
	I _{sc} (A)	0.88	0.73	1.47	2.24	2.94	4.48	
	Power tolerance (%)	0 ~ +10%						
MECHANICAL CHARACTERISTICS	Module dimensions (mm)	379x126x27	351x305x27	514x379x27 x2pcs	375x767x27	514x379x60 x2pcs	375x767x60 x2pcs	
	Cell dimensions (mm)	78x31.2	39x52	78x52	39x156	78x52	39x156	
	Cell type	Poly / Mono crystalline silicon						
	No. of cells and connections	12 (3x4)	36 (6x6)	36 (4x9)	36 (2x18)	36 (4x9)	36 (2x18)	
	Front cover	3.2mm tempered glass cleaned by washing machine in-site						
	Encapsulant	High quality EVA (Ethylene-Vinyl Acetate) with doing continuous cross-linking tests in-site						
	Frame	Special Z-type frame made by anodized aluminum alloy						
	Back cover	Fluoride-based backsheets in white or black color						
	Junction box	Small J-Box with fully silica potted for IP65 rated						
	Weight (kg)	0.6	1.1	2	3	4	6	
WARRANTY & TEMP. CHARACTERISTICS	NOCT	45 +/- 2°C						
	Temperature coefficient	P _{max} : -0.42 %/°C, V _{oc} : -0.34 %/°C, I _{sc} : 0.05 %/°C						
	Operating temperature range	-40°C ~ +80°C						
	Ambient temperature range	-40°C ~ +45°C						
	Certification	ISO 9001, ISO 14001, OHSAS 18001, CE						
	Product warranty	3 years						
Performance warranty	90% of power output for 10 years and 80% for 20 years							

At STC (1000W/m², 25°C, 1.5AM)

For more details or other specification not included above, please do feel free to contact with us via the information below

OPES Solutions GmbH

A: Zinnowitzer Strasse 1, 10115 Berlin - Germany

P: + 49 (0) 30-284 237 80

F: + 49 (0) 30-546 395 28

E: sales@opes-solutions.com

www.opes-solutions.com

OPES Solutions (Changzhou) Co., Ltd. – Factory

A: Building B1, Hutang Science and Technology Industrial

Park, Wujin District, Changzhou 213000, Jiangsu, China

P: +86 519 8188 9808

E: info@opes-solutions.com